

## XBO 6500 W/DHP IX OFR

XBO DHP for digital cinema projection | XBO品牌短弧氙灯



### 应用领域

- Cinema projection

### 产品特点

- Short arc with highest luminance for brighter screen illumination
- A lifetime of reliable performances with constant 6000 K color temperature
- Easy to maintain
- High level of arc stability
- Hot restart and instant light on screen
- Dimmable in a wide range



产品数据表

技术参数

电参数

|        |              |
|--------|--------------|
| 标称电流   | 165 安培       |
| 标称功率   | 650000 W     |
| 电流控制范围 | 133...173 安培 |
| 标称电压   | 390 V        |

尺寸和重量

|                   |                        |
|-------------------|------------------------|
| 直径                | 785 mm                 |
| 长度                | 4360 mm                |
| 含灯头长度 (不含针脚/连接装置) | 393.00 mm              |
| 输入端线缆长度           | 155 mm                 |
| 光中心 (LCL)         | 170.5 mm <sup>1)</sup> |
| 冷电极间隙             | 8.1 mm                 |
| 产品重量              | 100000 g               |
| 接线长度              | 1550                   |

<sup>1)</sup> 灯头末端至电极(冷)末梢距离

温度

|              |        |
|--------------|--------|
| 夹点处允许的最高环境温度 | 230 °C |
|--------------|--------|

寿命

|                           |        |
|---------------------------|--------|
| 寿命                        | 1000 h |
| Service Warranty Lifetime | 1200 h |

更多的产品数据

|             |           |
|-------------|-----------|
| 阳极灯头 (标准名称) | SFa30-7.9 |
| 阴极灯头 (标准名称) | SFaX30-14 |

功能

|      |                   |
|------|-------------------|
| 散热   | 强制                |
| 燃点位置 | h90 <sup>1)</sup> |

<sup>1)</sup> 垂直燃点位置: 正极(+)位于上端

Environmental information

|                                                                       |               |
|-----------------------------------------------------------------------|---------------|
| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |               |
| Date of Declaration                                                   | 07-07-2023    |
| Primary Article Identifier                                            | 4062172363792 |

产品数据表

|                                  |         |
|----------------------------------|---------|
| Declaration No. in SCIP database | In work |
|----------------------------------|---------|

产品数据表

安全建议

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

物流数据

| 产品代码          | 产品描述                     | 包装单位 ( 件/单位 ) | 尺寸 ( 长 x 宽 x 高 )            | 体积                    | 毛重        |
|---------------|--------------------------|---------------|-----------------------------|-----------------------|-----------|
| 4062172363792 | XBO 6500 W/DHP IX<br>OFR | 箱<br>1        | 590 mm x 234 mm x<br>234 mm | 32.31 dm <sup>3</sup> | 2149.00 g |

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时，按一个或多个整件数下单。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。