

XBO 3000 W/DTS OFR

XBO DTP for digital cinema projection | XBO品牌短弧氙灯

应用领域

- Cinema projection



产品特点

- Short arc with highest luminance for brighter screen illumination
- A lifetime of reliable performances with constant 6000 K color temperature
- Easy to maintain
- High level of arc stability
- Hot restart and instant light on screen
- Dimmable in a wide range








产品数据表

技术参数

电参数

标称电流	105 安培
标称功率	300000 W
电流控制范围	77113 安培
标称电压	290 V

尺寸和重量



直径	600 mm
长度	3350 mm
含灯头长度 (不含针脚/连接装置)	285.00 mm
光中心 (LCL)	125.0 mm ¹⁾
冷电极间隙	4.8 mm
产品重量	52000 g

¹⁾ 灯头末端至电极(冷)末梢距离

温度

夹点处允许的最高环境温度 230 ℃	
--------------------	--

寿命

寿命	1200 h
Service Warranty Lifetime	1500 h

更多的产品数据

阳极灯头 (标准名称)	SFa30-14
阴极灯头 (标准名称)	SFc30-14

功能

产品数据表

散热	强制
燃点位置	s 15 p 15 ¹⁾

¹⁾ 垂直燃点位置: 正极(+)位于上端

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Date of Declaration	06-03-2024	
Primary Article Identifier	4008321645050 4008321865519 4062172030489	
Candidate List Substance 1	Lead	
CAS No. of substance 1	7439-92-1	
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.	
Declaration No. in SCIP database	78e1128f-b105-4cf7-b75e-d67dd1f18348	

产品数据表

安全建议

Because of their high luminance, UV radiation and internal pressure in both the hot and cold state, XBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Xenon lamps are highly explosive. When hot, xenon lamps can cause burn marks. They should only be handled when the lamp is at room temperature. Always use the protective jackets supplied when handling these lamps. When packing the lamps and when installing or removing the lamps without their protective jackets, always wear protective clothing (face shield with neck protector, protective jacket and lint-free, cut-resistant gloves). For more information see the relevant in-pack leaflets and operating instructions.

物流数据

产品代码	产品描述	包装单位(件 / 单位)	尺寸(长x宽x高)	体积	毛重
4062172030489	XBO 3000 W/DTS OFR	箱 1	500 mm x 204 mm x 204 mm	20.81 dm³	1316.00 g

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时,按一个或多个整件数下 单。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。