

## LINEARlight FLEX Colormix Protect

线性LED软灯带 适用于灵活和个性化的照明解决方案



### 产品特点

- 软性、可分割LED灯带，带内嵌多芯片RGB LED
- 防护级别：IP67
- 防盐雾

### 产品优势

- 均匀变色
- 灵活的可切割式模块带来了极大的设计自由性
- 高性能硅，超长寿命、超灵活
- 得益于背侧自粘胶带，可以方便地安装在各种光滑表面上
- 非凡设计、高品质材料
- 通过可选CONNECTsystem实现免工具连接

### 应用领域

- 正面重点照明
- 建筑物中的特效照明
- 边缘耦合
- 道路照明
- 适合户外使用

## 产品系列数据表

### 设备/配件

- 简化了可选匹配连接系统的连接
- 采用可选细长滑轨系统，可以快速完成安装过程
- 可与24 V OPTOTRONIC电子镇流器完美搭配使用

### 应用建议

更多详细应用信息和图形,请参阅产品数据表。

### 数据表文本

- not relevant
- not relevant
- not relevant
- Avoid installations in rural and urban areas with high industrial activity and heavy traffic (higher than class than 4C1 according IEC 60721-3) and as well as installation in spa, areas with chlorine atmosphere, direct exposure to blown sand.

### 销售和技术支持

销售和技术支持 [www.osram.cn](http://www.osram.cn)

### Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015. The contained light source is intended for use in applications requiring high-quality coloured light.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。