

OT 240/220...240/24 DIM P

CV Power supplies 24 V with 1...10 V | 24 V 恒压 LED 电源 (电压 1...10 V)



应用领域

- 适用于室内外设施

产品数据表

技术参数

电参数

标称输出功率	240 W ¹⁾
市电频率	50...60 Hz
初级/次级电气隔离	3.75 kV ²⁾
设备功率损耗	21 W ³⁾
标称输出电压	24 V ⁴⁾
浪涌电流	70 安培 ⁵⁾
交流输入电压	198...264 V ⁶⁾
功率因数 λ	0.95/0.9 ⁷⁾
标称电压	220...240 V
标称电流	1.10 安培 ⁸⁾

- 1) 分载 0...240 W
- 2) SELV
- 3) 最大
- 4) +1.0/-0.5 V
- 5) 最大 / 在 250 μs
- 6) 允许电压范围
- 7) 最小/230 V时达到满负荷/230 V半载条件下
- 8) 在 230 V

尺寸和重量



安装孔距, 长度	241.0 mm
安装孔距, 宽度	16.0 mm
产品重量	1500.00 g
长度	250.0 mm
宽度	80.0 mm
高度	39.0 mm

产品数据表

温度

相对湿度	5...85 % ¹⁾
环境温度范围	-25...+55 °C

¹⁾ 不凝固的

更多的产品数据

后继 EAN	4052899545908
--------	---------------

功能

适合带防护等级的固件	I
过热保护	自动可逆
过载保护	自动可逆
Short-circuit protection	自动可逆
标准空载符合	是
调光界面	1...10 V ¹⁾
可调光	是
Number of channels	1

¹⁾ Do not switch off by 1...10 V interface to avoid infringing the ErP regulations

认证与标准

防护类型	IP67
标准	根据 IEC 61347-1标准/根据 IEC 61347-2-13标准/根据 IEC 62384标准/根据 CISPR 15标准/根据 IEC 61000-3-2标准/根据 IEC 61000-3-3标准/根据 IEC 61547标准
认证标志 – 认证	CE / CB / RCM / EAC / ENEC 18 / BIS

物流数据

商品编码	850440829000
------	--------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	11-10-2022
Primary Article Identifier	4008321981714
Declaration No. in SCIP database	In work

下载数据

产品数据表

文件	
	Addon Technical Information 728639_Dimming table for OT (EN)
	小册子 OPTOTRONIC constant-voltage LED power supplies and controls (EN)
	小册子 730792_Light is universal - Easy installation of efficient complete systems (DE)
	小册子 730791_Light is universal - Easy installation of efficient complete systems (EN)
	小册子 493514_24V OPTOTRONIC outdoor drivers (GB)
	证书 545904_ENEC certificate-117-N OT 240220-24024 DIM P
	统一宣言 OT 24V P DIMP CE 3537796 09 080823

Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

物流数据

产品代码	产品描述	包装单位 (件/单位)	尺寸 (长 x 宽 x 高)	体积	毛重
4008321981714	OT 240/220...240/24 DIM P	箱 8	540 mm x 193 mm x 400 mm	41.69 dm ³	14460.00 g

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时，按一个或多个整件数下单。

免责声明

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.