

OPTOTRONIC FIT D L

线型 / 面型恒流灯 – 不可调光



应用领域

- 按照 IEC 61347-2-13 标准附录 J 的要求安装在应急照明系统
- 适用于符合标准 EN60598-2-22 的应急照明系统中的设施
- 适合 I 类保护的灯具

产品优势

- 小型外壳设计

产品特点

- 线路频率 : 0 Hz | 50 Hz | 60 Hz
- 电源电压 : 220 至 240 V

产品系列数据表

应用建议

更多详细应用信息和图形,请参阅产品数据表。

销售和技术支持

销售和技术支持 www.osram.cn

Ecodesign regulation information:

Intended for use with LED modules.
The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。