

XENARC NIGHT BREAKER LASER D3S

最明亮的欧司朗氙气灯



亮度提升高达**200%**
照射距离更远，驾驶人员可以反应更迅速，与最低法律标准相比



照路距离高达**250米**
具有更高能见度



色温提升可达**20%**
Close to laser look compared to the minimum legal standard



欧司朗功率最强的氙气灯

氙气灯 NIGHT BREAKER LASER 是适用于你摩托车的最亮的车灯。这款强大的车灯拥有先进的氙气技术，确保能见度，与最低法律相比，增亮高达200%。更多的光线使司机有更好的视野，因此反应更迅速。同时具有长达250 m的远光，增加高达20%的白光（与最低法律标准相比）-接近激光外观。探索更佳表现的XENARC NIGHT BREAKER LASER -来自欧司朗最强的氙气灯，现有型号：D1S, D2S, D3S 和 D4S. 请注意，氙气灯应由专业技师去安装替换。

产品数据表

技术参数

电参数

功率输入	35 W
标称电压	42.0 V
标称功率	35.00 W
输入功率容许偏差	±3 %
测试电压	13.5 V

光度数据

光通量	3200 lm
色温	4400 K
光通量容许偏差	±15 %

尺寸和重量



长度	83.2 mm
直径	9 mm
产品重量	60.20 g

寿命

Lifespan B3	2000 h
使用寿命 Tc	3000 h

更多的产品数据

灯头 (标准名称)	PK32d-5
-----------	---------

功能

Technology	HID
------------	-----

产品数据表

认证与标准

ECE 分类	D3S ¹⁾
认证标志 – 认证	E1 认证

¹⁾ 仅可使用经过认证的电子控制装置运行

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (RECh)	
Date of Declaration	06-03-2024
Primary Article Identifier	4052899993150 4052899993136 4052899993112 4052899993099 4052899992979
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	83497fdb-f0d9-456b-bd77-0d812a8e2775 cfe441c2-c423-4f33-a5b0-b2a8b7592c15 d751e109-de28-4acf-9d59-e29beb418a68

物流数据

产品代码	产品描述	包装单位 (件/单位)	尺寸 (长 x 宽 x 高)	体积	毛重
4052899992979	XENARC NIGHT BREAKER LASER D3S	纸盒 1	53 mm x 46 mm x 93 mm	0.23 dm ³	83.00 g
4052899992986	XENARC NIGHT BREAKER LASER D3S	箱 4	115 mm x 101 mm x 103 mm	1.20 dm ³	346.00 g
4052899582491	XENARC NIGHT BREAKER LASER D3S	箱 48	371 mm x 256 mm x 232 mm	22.03 dm ³	4533.00 g
4052899993150	XENARC NIGHT BREAKER LASER D3S	塑料盒 2	- x - x -		89.00 g
4052899993167	XENARC NIGHT BREAKER LASER D3S	箱 10	257 mm x 129 mm x 121 mm	4.01 dm ³	1142.00 g

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时，按一个或多个整件数下单。

安全建议

XENARC lamps should be replaced by a qualified mechanic.

This product must only be operated with approved electronic control gear.

法律建议

Light output compared to the minimum ECE R98/99 requirements

产品数据表

This product must only be operated with approved electronic control gear

XENARC lamps should be replaced by a qualified mechanic

Reduced UV emission | For projection headlights | ECE approval and DOT label

± 450 lm

应用建议

更多详细应用信息和图形,请参阅产品数据表。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。

