

XENARC NIGHT BREAKER LASER D1S

最明亮的欧司朗氙气灯



亮度提升高达**200%**
照射距离更远，驾驶人员可以反应更迅速，与最低法律标准相比



照路距离高达**250米**
具有更高能见度



色温提升可达**20%**
Close to laser look compared to the minimum legal standard



欧司朗功率最强的氙气灯

氙气灯 NIGHT BREAKER LASER 是适用于你摩托车的最亮的车灯。这款强大的车灯拥有先进的氙气技术，确保能见度，与最低法律相比，增亮高达200%。更多的光线使司机有更好的视野，因此反应更迅速。同时具有长达250 m的远光，增加高达20%的白光（与最低法律标准相比）-接近激光外观。探索更佳表现的XENARC NIGHT BREAKER LASER -来自欧司朗最强的氙气灯，现有型号：D1S, D2S, D3S 和 D4S. 请注意，氙气灯应由专业技师去安装替换。

产品数据表

技术参数


电参数

功率输入	35 W
标称电压	850 V
标称功率	3500 W
输入功率容许偏差	±3 %
测试电压	13.5 V

光度数据

光通量	3200 lm
色温	4500 K
光通量容许偏差	±15 %

尺寸和重量



长度	832 mm
直径	900 mm
产品重量	5900 g

寿命

Lifespan B3	1500 h
使用寿命 Tc	3000 h

更多的产品数据

灯头 (标准名称)	PK32d-2
-----------	---------

功能

Technology	HID
------------	-----

产品数据表

认证与标准

ECE 分类	D1S ¹⁾
认证标志 – 认证	E1 认证

¹⁾ 仅可使用经过认证的电子控制装置运行

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (RECh)	
Date of Declaration	06-03-2024
Primary Article Identifier	4052899993075 4052899993051 4052899993037 4052899993013 4052899992870
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	ccb03c4a-a29c-4abe-920d-8f9616541d50 99f64b8f-b549-4139-9e34-d3907343674d 281f73d6-719d-4570-a537-1f78ed0a9f77

物流数据

产品代码	产品描述	包装单位 (件/单位)	尺寸 (长 x 宽 x 高)	体积	毛重
4052899992870	XENARC NIGHT BREAKER LASER D1S	纸盒 1	53 mm x 46 mm x 93 mm	0.23 dm ³	81.00 g
4052899992887	XENARC NIGHT BREAKER LASER D1S	箱 4	115 mm x 101 mm x 103 mm	1.20 dm ³	348.00 g
4052899582477	XENARC NIGHT BREAKER LASER D1S	箱 48	371 mm x 256 mm x 232 mm	22.03 dm ³	4423.00 g
4052899993075	XENARC NIGHT BREAKER LASER D1S	塑料盒 2	- x - x -		89.00 g
4052899993082	XENARC NIGHT BREAKER LASER D1S	箱 10	257 mm x 129 mm x 121 mm	4.01 dm ³	1147.00 g

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时，按一个或多个整件数下单。

安全建议

XENARC lamps should be replaced by a qualified mechanic.

This product must only be operated with approved electronic control gear.

法律建议

Light output compared to the minimum ECE R98/99 requirements

产品数据表

This product must only be operated with approved electronic control gear

XENARC lamps should be replaced by a qualified mechanic

Reduced UV emission | For projection headlights | ECE approval and DOT label

± 450 lm

应用建议

更多详细应用信息和图形,请参阅产品数据表。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。

