

BA-M-CP-840 G4

BackLED M Plus G4 | 招牌和背光照明用 LED 模块



产品优势

- 一致性好的白色光 (标准颜色偏差与 SDCM 相当 : < 3)

应用领域

- 中型尺寸通道文字的背光照明



产品数据表

技术参数

电参数

标称电压	12.0 V
单链标称功率	28.80 W
单个 LED 模块的标称功率	0.72 W
Accidental reverse input voltage protection up to	13 V
输入电压范围	12...13 V
电流类型	DC


光度数据

色温	4000 K
显色指数 Ra	≥80
EN 12464-1 标准光色	白色
LED 光色	白色
单个模块链的光通量	3280 lm
单个 LED 模块的光通量	82 lm
发光效率	113.9 lm/W
色彩匹配标准偏差	≤3 sdcn

LED 模块信息

模块LED颗粒数	3
单个链中的 LED 模块数量	40
LED 模块的最小可操作数量	1

尺寸和重量



长度	8168 mm
宽度	13.8 mm
高度	6.80 mm

产品数据表

产品重量	270.00 g
Module length	47.5 mm
Module pitch	200 mm

温度

仓储温度范围	-30...85 °C
--------	-------------

更多的产品数据

ID of contained light source [AGGR]	LS_SHZ_600426
后继 EAN	4052899593022

功能

可调光	是
调光范围	1...100 %

认证与标准

能耗	29 kWh/1000h
防护类型	IP66
认证标志 – 认证	BIS / CE
Energy efficiency class of the contained light source	F

物流数据

商品编码	85395100000
------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	21-08-2023
Primary Article Identifier	4062172183376
Candidate List Substance 1	Lead
CAS No. of substance 1	7439-92-1
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.
Declaration No. in SCIP database	b8b42c6d-71d8-4063-b9cf-23e1f521e4b9

下载数据

文件

产品数据表

	User instruction BackLED SM CP G4 UI OSRAM
	小册子 Technical application guide BackLED and BoxLED portfolio (EN)
	统一宣言 CE declaration BA M CP G4

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

物流数据

产品代码	产品描述	包装单位 (件/单位)	尺寸 (长 x 宽 x 高)	体积	毛重
4062172183376	BA-M-CP-840 G4	箱 50	435 mm x 435 mm x 310 mm	58.66 dm ³	15281.00 g

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时，按一个或多个整件数下单。

可选择性配件

产品描述	配件名称	配件代码
BA-M-CP-840 G4	BA -MP-M-CP-2	▶ 4062172168410

免责声明

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.