

PL-LIN-Z6 2200-827 560X20-HV

PrevaLED Linear G6 | 线型LED 模组



产品特点

- 可用光通量：2200 lm 或 4000 lm (560 mm 时)

产品优势

- High voltage (HV) optimized for non-isolated, low voltage (LV) optimized for SELV operation

应用领域

- Office
- 工业



产品数据表

技术参数

电参数

标称电压	471 V
标称电流	025 安培
电流类型	DC
On-mode power [AGGR]	12.20 W
Energy consumption in on-mode [AGGR]	12.2 kWh/1000h

光度数据

发光效率	177 lm/W
显色指数 Ra	80
Correlated color temperature CCT [AGGR]	2700 K
Colour consistency (McAdam ellipses) [AGGR]	3
Useful luminous flux (Φuse) [AGGR]	1977 lm

光参数

启动时间	< 01 s
升温时间 (60 %)	< 200 s

LED 模块信息

模块LED颗粒数	72
----------	----

尺寸和重量



产品重量	4000 g
Height EPREL [AGGR]	5.0 mm
Length EPREL [AGGR]	560.0 mm
Width EPREL [AGGR]	20.0 mm

产品数据表

温度

符合 IEC 62717 的性能温度	50 °C
工作温度范围	-20...75 °C
温度系数测试点最高温度	75 °C
仓储温度范围	-30...85 °C
环境温度范围	-20...+75 °C

寿命

点亮次数	100000
Lumen maintenance factor LMF [AGGR]	96
L70B50 lifetime [AGGR]	100000 h

更多的产品数据

Lighting technology used [AGGR]	LED
---------------------------------	-----

认证与标准

标准	CE/ENEC/VDE
防护类型	IP20
Energy efficiency class [AGGR]	D

物流数据

商品编码	85395100000
------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4052899606265
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

产品数据表



PL LIN G5 G6 Mounting Guidance 251021

数据表文本

- When parallel wiring, tolerance-related differences in output are possible and may cause deviations in brightness.

下载数据

文件	
	证书 PL ENEC 40031612 250723
	统一宣言 PL LIN Z6 CE 3812352 090823
	CAD数据3 PL LIN Z5 Z6 2200 560x20 HV CADPDF 240220

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

物流数据

产品代码	产品描述	包装单位 (件/单位)	尺寸 (长 x 宽 x 高)	体积	毛重
4052899606265	PL-LIN-Z6 2200-827 560X20-HV	箱 120	588 mm x 380 mm x 125 mm	27.93 dm ³	5347.00 g

产品数据表

物流数据

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时，按一个或多个整件数下单。

免责声明

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.