

BA-LIN-Z3 4400-830 1120X20

BASIC Linear G3 | 线型LED 模组



应用领域

- Office
- 工业



产品数据表

技术参数

电参数

|                                      |                |
|--------------------------------------|----------------|
| 标称电压                                 | 982 V          |
| 标称电流                                 | 025 安培         |
| 电流类型                                 | DC             |
| On-mode power [AGGR]                 | 24.60 W        |
| Energy consumption in on-mode [AGGR] | 24.6 kWh/1000h |

光度数据

|                                             |          |
|---------------------------------------------|----------|
| 发光效率                                        | 161 lm/W |
| 显色指数 Ra                                     | 82       |
| Correlated color temperature CCT [AGGR]     | 3000 K   |
| Colour consistency (McAdam ellipses) [AGGR] | 3        |
| Useful luminous flux (Φuse) [AGGR]          | 3955 lm  |


光参数

|             |         |
|-------------|---------|
| 启动时间        | < 01 s  |
| 升温时间 (60 %) | < 200 s |

LED 模块信息

|          |     |
|----------|-----|
| 模块LED颗粒数 | 144 |
|----------|-----|

尺寸和重量



|                     |           |
|---------------------|-----------|
| 产品重量                | 4830 g    |
| Height EPREL [AGGR] | 5.0 mm    |
| Length EPREL [AGGR] | 1120.0 mm |
| Width EPREL [AGGR]  | 20.0 mm   |

产品数据表

温度

|                    |              |
|--------------------|--------------|
| 符合 IEC 62717 的性能温度 | 50 °C        |
| 工作温度范围             | -20...75 °C  |
| 温度系数测试点最高温度        | 75 °C        |
| 仓储温度范围             | -30...85 °C  |
| 环境温度范围             | -20...+75 °C |

寿命

|                                     |         |
|-------------------------------------|---------|
| 点亮次数                                | 100000  |
| Lumen maintenance factor LMF [AGGR] | 96      |
| L70B50 lifetime [AGGR]              | 50000 h |

更多的产品数据

|                                 |               |
|---------------------------------|---------------|
| Lighting technology used [AGGR] | LED           |
| 后继 EAN                          | 4052899989900 |

认证与标准

|                                |             |
|--------------------------------|-------------|
| 标准                             | CE/ENEC/VDE |
| 防护类型                           | IP20        |
| Energy efficiency class [AGGR] | D           |

物流数据

|      |             |
|------|-------------|
| 商品编码 | 85414100000 |
|------|-------------|

Environmental information

|                                                                       |                                    |
|-----------------------------------------------------------------------|------------------------------------|
| Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH) |                                    |
| Date of Declaration                                                   | 18-04-2022                         |
| Primary Article Identifier                                            | 4052899607682                      |
| Candidate List Substance 1                                            | No declarable substances contained |
| Declaration No. in SCIP database                                      | No declarable substances contained |

产品数据表



484525\_5 Year Osram Guarante  
(GB)

下载数据

| 文件                                                                                  |                                     |
|-------------------------------------------------------------------------------------|-------------------------------------|
|    | User instruction<br>BASIC Linear G3 |
|   | 证书<br>PL ENEC 40031612 250723       |
|  | 统一宣言<br>BA LIN Z3 CE 3803980 060921 |

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

物流数据

| 产品代码          | 产品描述                          | 包装单位 ( 件/单位 ) | 尺寸 ( 长 x 宽 x 高 )             | 体积                    | 毛重        |
|---------------|-------------------------------|---------------|------------------------------|-----------------------|-----------|
| 4052899607682 | BA-LIN-Z3 4400-830<br>1120X20 | 箱<br>120      | 1141 mm x 380 mm x 125<br>mm | 54.20 dm <sup>3</sup> | 6682.00 g |

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时，按一个或多个整件数下单。

免责声明

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.