

OPTOTRONIC Intelligent Industry – DEXAL (non-isolated)

线性LED恒流驱动电源-调光



应用领域

- Industry lighting
- 适合I类保护的灯具

产品优势

- Versatile non-isolated DEXAL LED driver up to 150 W due to flexible output characteristic
- 较高的浪涌防护等级：最高4 kV (L-N) / 4 kV (L/N-PE)

产品特点

- 线路频率：0 Hz | 50 Hz | 60 Hz
- 监控全套照明装置的工作参数
- 电源电压：220至240 V
- Available with output current range: up to 850 mA

产品系列数据表

应用建议

更多详细应用信息和图形,请参阅产品数据表。

数据表文本

- The DEXAL interface is polarity sensitive, even if the DEXAL bus power supply in the driver is turned off. Therefore the polarity of all connected drivers should not be mixed.
- For efficiency and standby power measurement, the D4i bus power supply shall be switched off by using Tuner4TRONIC. Refer to www.tuner4tronic.com.

销售和技术支持

销售和技术支持 www.osram.cn

Ecodesign regulation information:

Intended for use with LED modules.

The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。