

LEDDriving HL CBI



路面照射亮度提升
有效照射区域增亮+320%



照射距离更远
车前有效照射距离增远+100米



高性能LED芯片使用，即刻点亮



产品系列数据表

技术参数

产品描述	Product information			光度数据	寿命	功能
	Order reference	Product type (off-road vs. on-road)	Application (Category and Product specific)	光通量	使用寿命 Tc	Technology
LEDriving HL CBI ≙ HB/LB	LEDPE5105-BK 12	Off-road ≙ HB/LB	Mainly used for headlight applications	2000/2600 lm ¹⁾	5000 h	LED

产品描述	Environmental information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
	Date of Declaration	Primary Article Identifier	Declaration No. in SCIP database
LEDriving HL CBI ≙ HB/LB	07-03-2024	4062172090414 4062172145121 4062172200301 4062172302883	In work

¹⁾ LB/HB

下载数据

文件	
	小册子 LEDriving Retrofits - Exchange overview (EN)
	产品电影 PFR Bi-function projector (EN)
	360 Degree Image OSRAM LEDriving CBI

应用建议
更多详细应用信息和图形,请参阅产品数据表。

免责声明
更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。

