

DALI PRO 2 IOT

DALI PRO 2 IOT | 控制器-照明控制系统



产品特点

- DALI-2 certified
- IoT ready with built-in gateway for remote data access
- Easy browser-based commissioning UI and Professional Software available
- Small form factor: only 6 TE (DIN rail)
- Commissioning via Ethernet/WLAN

产品优势

- DALI-2 certified for improved multi-vendor interoperability
- Template based onsite commissioning via Smart device
- Building Management System integration via optional KNX interface
- Remote access for changes in the configuration from every location
- LAN Interconnect to connect up-to 8 Controllers into one network
- Rest API for connection of a 3rd party Cloud with the DALI Pro2 IoT Controller
- Automated testing and reporting of emergency lighting installations
- Daylight Simulation via scene recall and/or light sensor regulation

应用领域

- 房间控制、地板控制和日光相关控制
- 连接DALI系统中照明和存在传感器
- RGB and Tunable white applications
- 会议室
- 办公室
- 适用于室内应用
- 工业
- 灯带
- 教室
- 体育馆


产品数据表

技术参数

电参数

标称电压	220...240 V
市电频率	50/60 Hz
系统功率 [AGGR]	2000 W

尺寸和重量



高度	620 mm
产品重量	24700 g
长度	910 mm
宽度	1060 mm

温度

环境温度范围	0...+40 °C
--------	------------

功能

安装类型	Din Rail
Scenes	512 ¹⁾
Max. connectable push button couplers	16 ²⁾
App Control	Yes (Android/ iOS)
Commissioning tool	PC Tool (Windows) / WebUI
Max. number of connected controllers	8

¹⁾ Each DALI ECG can store up to 16 light scenes.

²⁾ Max number pro DALI line. The actual number depends on the total number of DALI devices (couplers, sensors and ECGs) connected on the same DALI line

物流数据

商品编码	85371091990
------	-------------

产品数据表

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-08-2023
Primary Article Identifier	4062172114189
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

设备/配件

- Easy browser-based commissioning UI (for smart devices)

下载数据

文件	
	User instruction DALI Pro 2 IoT
	小册子 Light is IoT ready - DALI PRO 2 IoT (EN)
	统一宣言 DALI Pro 2 IoT CE 41966710 160920
	CAD数据 DALI PRO 2 IoT IGS 280120
	CAD数据 DALI PRO 2 IoT STEP 280120
	CAD数据2 DALI PRO 2 IoT CAD2PDF 280120
	CAD数据3 DALI PRO 2 IoT CAD3PDF 280120

物流数据

产品代码	产品描述	包装单位 (件/单位)	尺寸 (长 x 宽 x 高)	体积	毛重
4062172114189	DALI PRO 2 IOT	箱 20	235 mm x 199 mm x 372 mm	17.40 dm³	5905.00 g

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时，按一个或多个整件数下单。

参考资料/链接

产品数据表

Expert configuration software available at

▶ www.osram.com/software

免责声明

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.