

LR-P-2000 -927-10S-BK-15-TB-G1

LINEARlight Rigid FINESSE |



产品特点

- Slim, modular LED fixture for linear applications, fully customizable
- Several optics, Wall Grazing and WallWashing; 10°, 30°, 60°
- Outdoor IP67 or Indoor IP43 versions available
- Large operating temperature range: from -30 ° to +50 ° Celsius
- Luminous flux: > 2000 lm/m; 1200 lm/m; 900 lm/m
- Color uniformity ≤ 2 SDCM
- Lifetime up to 60.000 h L80B10; LM80 and LM79
- Large selection of color temperatures: 2400 K – 5000 K; CRI 80, CRI 90
- Dimmable by OPTOTRONIC LED driver from 0 % to 100 %
- Designed in Italy, made in Germany
- Durable, coated aluminum profile resistant to harsh environments: AMA

产品优势

- 15 lengths available to adapt to all conditions
- Easy to configure the desired light performance for optimal illumination
- Protected against the atmospheric agents: from the desert to the glacier
- Long-time functionality and maintenance-free
- High color fidelity to beautify every design
- Fully controllable by most used light control protocols: DALI, DMX
- Color consistent with LINEARlight FLEX products
- Several installation accessories available



产品数据表

应用领域

- Wall Grazing
- Ambient lighting
- Wall washing
- 暗槽照明
- Architectural integration

产品数据表

技术参数

Product information

Order reference	LR-P-2000-927-1
-----------------	-----------------

电参数

标称电压	240 V
Accidental reverse input voltage protection up to	25 V


光度数据

色温	2700 K
光通量	3300 lm
发光强度	5300 cd
EN 12464-1 标准光色	白色
显色指数 Ra	> 90
灯具效率	0.76
发光效率	76 lm/W
色温	2700 K

光参数

光束角	10 °
-----	------

尺寸和重量



长度	00 mm
宽度	250 mm
高度	330 mm
产品重量	150000 g
产品重量	0

产品数据表

颜色和材料

灯体材料	铝
产品颜色	黑色
面板材质	聚碳酸酯

温度

环境温度范围	-30...+50 °C
--------	--------------

寿命

寿命	60000 h
----	---------

功能

可调光	是
-----	---

认证与标准

防护类型	IP67
------	------

特定分类

Order reference	LR-P-2000-927-1
-----------------	-----------------

物流数据


商品编码	94051190900
------	-------------

Environmental information


Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	27-05-2022
Primary Article Identifier	4062172144896
Declaration No. in SCIP database	In work

产品数据表


光分布




LRF-930-120D-G1 Illuminance Cone Diagram



LRF-930-90T-G1 Illuminance Cone Diagram




LRF-930-60S-G1 Illuminance Cone Diagram




LRF-930-30S-G1 Illuminance Cone Diagram


产品数据表



LRF-930-10S G1 Illuminance Cone Diagram



LRF-930-10B-G1 Illuminance Cone Diagram



LRF-930-WW-G1 Illuminance Cone Diagram

下载数据

文件

产品数据表

	User instruction FINESSE
	User instruction FINESSE RGB RGBW
	Product Datasheet LINEARlight RIGID FINESSE (EN)
	Product Datasheet LINEARlight RIGID FINESSE RGB (W) (EN)
	小册子 Light is awesome - LINEARlight Rigid FINESSE (EN)
	证书 Finesse LR P fixed CB 04032022
	证书 Finesse LR P fixed D 04032022
	证书 Finesse LR P fixed ENEC
	证书 Finesse LR P floodlighth CB 04032022
	证书 Finesse LR P floodlighth D 04032022
	证书 Finesse LR P floodlighth ENEC 04032022
	CAD数据 LRF-P-2000-ABC-XX-YY-02-ZZ-G1 STEP 070420
	CAD数据3 LRF-P-2000-ABC-XX-YY-03-ZZ-G1 STEP 070420
	CAD数据3 LRF-P-2000-ABC-XX-YY-04-ZZ-G1 STEP 070420
	CAD数据3 LRF-P-2000-ABC-XX-YY-05-ZZ-G1 STEP 070420
	CAD数据3 LRF-P-2000-ABC-XX-YY-06-ZZ-G1 STEP 070420
	CAD数据3 LRF-P-2000-ABC-XX-YY-07-ZZ-G1 STEP 070420
	CAD数据3 LRF-P-2000-ABC-XX-YY-08-ZZ-G1 STEP 070420
	CAD数据3 LRF-P-2000-ABC-XX-YY-09-ZZ-G1 STEP 070420
	CAD数据3 LRF-P-2000-ABC-XX-YY-10-ZZ-G1 STEP 070420
	CAD数据3 LRF-P-2000-ABC-XX-YY-11-ZZ-G1 STEP 070420
	CAD数据3 LRF-P-2000-ABC-XX-YY-12-ZZ-G1 STEP 070420
	CAD数据3 LRF-P-2000-ABC-XX-YY-13-ZZ-G1 STEP 070420

产品数据表

	CAD数据3 LRF-P-2000-ABC-XX-YY-14-ZZ-G1
	CAD数据3 LRF-P-2000-ABC-XX-YY-15-ZZ-G1
	Eulumdat LR-x-2000-930-10B-xx-10-xx-G1 LTD
	Eulumdat LR-x-2000-930-10S-xx-10-xx-G1 LTD
	Eulumdat LR-x-2000-930-120D-xx-10-xx-G1 LTD
	Eulumdat LR-x-2000-930-30S-xx-10-xx-G1 LTD
	Eulumdat LR-x-2000-930-60S-xx-10-xx-G1 LTD
	Eulumdat LR-x-2000-930-90T-xx-10-xx-G1 LTD
	Eulumdat LR-x-2000-930-WW-xx-10-xx-G1 LTD
	IES data LR-x-2000-930-10B-xx-10-xx-G1 IES
	IES data LR-x-2000-930-10S-xx-10-xx-G1 IES
	IES data LR-x-2000-930-120D-xx-10-xx-G1 IES
	IES data LR-x-2000-930-30S-xx-10-xx-G1 IES
	IES data LR-x-2000-930-60S-xx-10-xx-G1 IES
	IES data LR-x-2000-930-90T-xx-10-xx-G1 IES
	IES data LR-x-2000-930-WW-xx-10-xx-G1 IES

产品数据表

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

物流数据

产品代码	产品描述	包装单位 (件/单位)	尺寸 (长 x 宽 x 高)	体积	毛重
4062172144896	LR-P-2000 -927-10S-BK-15-TB-G1	箱 6	1638 mm x 121 mm x 111 mm	22.00 dm³	10043.00 g

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时，按一个或多个整件数下单。

免责声明

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.