

## PrevaLED Linear TW G2

### 线型LED 模组



#### 产品特点

- Module efficacy: up to 170 lm/W with 2,700K
- Module efficacy: up to 190 lm/W with 6,500K
- Available module length: 62 mm, 280 mm, 560 mm
- Available with luminous flux: 245 lm, 1,100 lm and 2,200 lm
- 初始颜色一致性 :  $\leq 3$  SDCM
- Average lifetime (L80 B50): up to 70,000 h (temperature at  $T_c = 55^\circ\text{C}$ )

#### 产品优势

- SELV or non-isolated LED Module with perfect match to Optotronic TW driver

#### 应用领域

- 办公室
- Education

## 产品系列数据表

---

### 应用建议

更多详细应用信息和图形,请参阅产品数据表。

---

### 销售和技术支持

销售和技术支持 [www.osram.cn](http://www.osram.cn)

---

### Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

---

### 免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。