

PL-LIN-Z2 2200-9TW 560-LV/1A4

PrevaLED Linear TW G2 | 线型LED 模组



产品特点

- Module efficacy: up to 170 lm/W with 2,700K
- Module efficacy: up to 190 lm/W with 6,500K
- Available module length: 62 mm, 280 mm, 560 mm
- Available with luminous flux: 245 lm, 1,100 lm and 2,200 lm
- 初始颜色一致性 : ≤ 3 SDCM
- Average lifetime (L80 B50): up to 70,000 h (temperature at $T_c = 55^\circ\text{C}$)

产品优势

- SELV or non-isolated LED Module with perfect match to Optotronic TW driver

应用领域

- 办公室
- Education



产品数据表

技术参数

电参数

标称电压	106 V
标称电流	13 安培
电流类型	DC
On-mode power [AGGR]	15.10 W
Energy consumption in on-mode [AGGR]	15.1 kWh/1000h

光度数据

发光效率	138157 lm/W
显色指数 Ra	90
Correlated color temperature CCT [AGGR]	6500 K
Colour consistency (McAdam ellipses) [AGGR]	3
Useful luminous flux (Φuse) [AGGR]	2145 lm

光参数

光束角	0 °
启动时间	< 01 s
升温时间 (60 %)	< 200 s

LED 模块信息

模块LED颗粒数	96
----------	----

尺寸和重量

产品重量	4000 g
Height EPREL [AGGR]	5.0 mm
Length EPREL [AGGR]	560.0 mm
Width EPREL [AGGR]	20.0 mm

温度

符合 IEC 62717 的性能温度	50 °C
工作温度范围	-20...75 °C
温度系数测试点最高温度	75 °C
仓储温度范围	-30...85 °C
环境温度范围	-20...+75 °C

寿命

点亮次数	100000
------	--------

产品数据表

Lumen maintenance factor LMF [AGGR]	96
L70B50 lifetime [AGGR]	50000 h

更多的产品数据

Lighting technology used [AGGR]	LED
---------------------------------	-----

功能

可调光	是
-----	---

认证与标准

标准	CE/ENEC
防护类型	IP20
Energy efficiency class [AGGR]	E

物流数据

商品编码	85395100000
------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	18-04-2022
Primary Article Identifier	4052899618558
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

下载数据

文件	
	证书 PL ENEC 40031612 250723
	统一宣言 PL LIN Z2 TW CE 4227114 141220

产品数据表

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

物流数据

产品代码	产品描述	包装单位 (件/单位)	尺寸 (长 x 宽 x 高)	体积	毛重
4052899618558	PL-LIN-Z2 2200-9TW 560-LV/1A4	箱 60	583 mm x 254 mm x 167 mm	24.73 dm ³	2971.00 g

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时，按一个或多个整件数下单。

免责声明

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.