

OPTOTRONIC - DIM (1-10V) ADJ IP66

恒流 – 可调光



应用领域

- Spot light and down light
- 街道和城区照明
- Industry lighting
- 适合I类保护的灯具

产品优势

- Easily current adjustment by potentiometer
- 较高的浪涌防护等级：最高6 kV
- 0...10 V dimming (minimum 10%)
- High efficiency up to 88%
- Wide output voltage & current range for multiple applications
- Double isolation between primary/secondary sides (SELV)
- Over temperature protection
- IP66 (Independent installation)
- Very low ripple < 3%

产品系列数据表

应用建议

更多详细应用信息和图形,请参阅产品数据表。

销售和技术支持

销售和技术支持 www.osram.cn

Ecodesign regulation information:

Intended for use with LED modules.
The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。