

VFP1000 G4-940-05

VALUE Flex Protect G4 | 线性LED软灯带 适用于灵活和个性化的照明解决方案



产品特点

- 3 SDCM, CRI90
- Non-IP and IP66 version available
- 120° viewing angle per module
- Up to 50,000 hrs lifetime @ tc max

产品优势

- Multi cut-able with CONNECT system

应用领域

- 酒店
- 招牌
- 建筑照明
- 墙壁整合



产品数据表

技术参数

电参数

标称电压	24.0 V
电流类型	DC
额定功率	50.00 W
输入电压范围	23...25 V
Accidental reverse input voltage protection up to	25 V

光度数据

LED 光色	白色
显色指数 Ra	>90
发光效率	98 lm/W
EN 12464-1 标准光色	白色

尺寸和重量



长度	5000 mm
产品重量	330.00 g
宽度	14.3 mm
高度	4.10 mm

温度

仓储温度范围	-25...70 °C
--------	-------------

认证与标准

标准	CE/Acc. to EN62471/EN62778/Acc. to IEC60838/IEC 60068-2-52 severity 1/ISO 4892-2 - Method A/RoHS/Reach
----	--

物流数据


产品数据表

商品编码	888888888888
------	--------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	19-01-2022
Primary Article Identifier	4062172153515
Declaration No. in SCIP database	In work

下载数据

文件	
	IES data IES OF VFP1000 940 G4

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer. In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer. Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

物流数据

产品代码	产品描述	包装单位 (件/单位)	尺寸 (长 x 宽 x 高)	体积	毛重
4062172153515	VFP1000 G4-940-05	箱 20	465 mm x 275 mm x 208 mm	26.60 dm ³	7660.00 g

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时，按一个或多个整件数下单。

免责声明

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.