OSRAM

LEDriving SL P21/5W WHITE

理想车辆的理想升级品



Suitable for various vehicle exterior applications

冷白可供选择

Replaces conventional P215W lamps

Easy upgrade to LED technology with plug & play solutions



Reliable OSRAM quality stands for less lamp replacements

4-year OSRAM guarantee (refer to www.osram.com/am-guarantee for precise conditions)



是P21/5W的LED替代品

LEDriving SL P21/5W replacement lamps offer a modern and intense light with a color temperature up to 6,000 Kelvin. These replacement lamps are suitable for all conventional P21/5W lamp bases. In comparison to standard lamps, these LED retrofit lamps use up to 80% less energy. OSRAM offers a 4 year guarantee for these LEDriving SL lamps. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

产品数据表

技术参数

Product information

Order reference	7528DWP	
Product type (off-road vs. on-road)	Off-road ≙ P21/5W	
Application (Category and Product specific)	Mainly used for signal/indicator applications	


电参数

功率输入	2.50 / 0.5 W
标称电压	12.0 V
标称功率	2.00/0.40 W
输入功率容许偏差	±25 %
测试电压	13.5 V

光度数据

色温	6000 К
光通量	145/30 lm
光通量容许偏差	±15 %
LED 光色	Cool white

尺寸和重量



长度	52.5 mm
直径	27.0 mm
产品重量	16.00 g

寿命

Lifespan B3	1500 h
使用寿命 Tc	4000 h
Guarantee	4 年

产品数据表

更多的产品数据

灯头 (标准名称)	BAY15d
-----------	--------

功能

 $^{^{1)}}$ Light-emitting diode lamp

特定分类

Order reference	7528DWP

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)			
Date of Declaration	09-02-2024		
Primary Article Identifier	4062172151726 4062172401197		
Candidate List Substance 1	Lead		
CAS No. of substance 1	7439-92-1		
Safe Use Instruction	The identification of the Candidate List substance is sufficient to allow safe use of the article.		
Declaration No. in SCIP database	026eb835-3aa5-4bfa-a635-bb4b42c468ab		

物流数据

产品代码	产品描述	包装单位(件 / 单位)	尺寸(长x宽x高)	体积	毛重
4062172151726	LEDriving SL ≙ P21/5W	吸塑 2	135 mm x 95 mm x 18 mm	0.23 dm ³	44.00 g
4062172151733	LEDriving SL ≙ P21/5W	箱 10	119 mm x 109 mm x 151 mm	1.96 dm ³	256.00 g

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时,按一个或多个整件数下 单。

下载数据

文件



小册子

LEDriving Retrofits - Exchange overview (EN)

安全建议

产品数据表

Canbus compatible

Coloured lamps for usage behind coloured glass

法律建议

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

应用建议

更多详细应用信息和图形,请参阅产品数据表。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。

