

ELEMENT G3

紧凑型LED恒流驱动电源-非调光



产品特点

- Fixed output (no dimming)
- Input voltage: 220 – 240 VAC
- Suitable for Class I/II luminaires
- Output current range 150-1050 mA
- Up to 30 000 h lifetime at $t_{cmax} = 80\text{ °C}$
- Typ. Efficiency: from 82% to 90% depend on different wattage
- SELV
- Ambient temp range, t_a : -20 °C to $+50\text{ °C}$

产品优势

- Safety ensured by OSRAM (SELV)
- High quality of light with ripple current $< 5\%$

应用领域

- Spot light and down light
- Panels
- Other Indoor LED luminaires

产品系列数据表

应用建议

更多详细应用信息和图形,请参阅产品数据表。

销售和技术支持

销售和技术支持 www.osram.cn

Ecodesign regulation information:

Intended for use with LED modules.
The forward voltage of the LED light source shall be within the defined operating window of the control gear in all operating conditions including dimming if applicable.

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。