

PL-CN50-COB- 1400-940-40D-G2

PrevaLED COIN 50 COB G2 | LED模块，带集成式光学器件和散热器



产品特点

- Color consistency < 2 SDCM
- TM30 compliant
- High flux output up to 1500 lm
- Beam angle: 15°, 24°, 40°
- 防护级别：IP20

产品优势

- Precise optical control and free from multi-shadow issue
- Replaceable front cover to maximize optics flexibility and future extension
- Dual mode options in High-Output (HO) and High-Efficacy (HE)

应用领域

- Retail, shop, restaurant, hospitality
- High-end residential
- 适用于室内应用
- Connecting multiple modules in parallel on one LED driver is not permitted
- Connecting multiple modules in series on one LED driver is not recommended
- Do not use in sealed fixtures
- Avoid covering the lens with dust or any object



产品数据表

技术参数

电参数

标称电流	0.35 安培
标称电压	36.5 V
电流类型	DC
On-mode power [AGGR]	12.50 W
Energy consumption in on-mode [AGGR]	12.5 kWh/1000h ¹⁾

1) _

光度数据

发光效率	104 lm/W
EN 12464-1 标准光色	4000 K
显色指数 Ra	90
Correlated color temperature CCT [AGGR]	3900 K
Peak luminous intensity [AGGR]	2450
Colour consistency (McAdam ellipses) [AGGR]	2
Useful luminous flux (Φuse) [AGGR]	1100 lm ¹⁾

1) 90°

光参数

启动时间	< 0.5 s
升温时间 (60 %)	< 2.00 s
光束角	40 °

产品数据表

尺寸和重量



直径	50.0 mm ¹⁾
产品重量	90.00 g
Height EPREL [AGGR]	55.0 mm
Length EPREL [AGGR]	50.0 mm
Width EPREL [AGGR]	50.0 mm

¹⁾ ±0.3 mm

颜色和材料

Heatsink color	Grey
----------------	------

温度

符合 IEC 62717 的性能温度	70 °C
温度系数测试点最高温度	90 °C
环境温度范围	-25...+40 °C
仓储温度范围	-40...80 °C

寿命

点亮次数	15000
------	-------

产品数据表

Lumen maintenance factor LMF [AGGR]	96 ¹⁾
L70B50 lifetime [AGGR]	50000 h ¹⁾

1) _

更多的产品数据

产品说明	Modules perfectly matched to OSRAM OPTOTRONIC LED drivers (see relevant table)/对当前光测定数据和重要的安全、安装和应用的信息,请查看 www.osram.com/led-systems/ 所有技术参数均适用于全部模组。由于发光二极管制造过程的复杂性, LED光色、寿命等标称参数值均为统计数值, 而不对应个体产品, 个体产品的实际参数值可能与标称值存在差异。/Tolerance for optical and electrical data: +/-10%
Lighting technology used [AGGR]	LED
后继 EAN	4052899541818

功能

可调光	是
-----	---

认证与标准

标准	根据 IEC 62471标准/根据 EN 60598-1标准/根据 EN 60529标准/根据 EN 55015标准/根据 EN 61547标准 /Acc. To EN62031 IEC 605981/CE
防护类型	IP20
Energy efficiency class [AGGR]	F

物流数据

商品编码	85395100000
------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	20-07-2022
Primary Article Identifier	4052899621329
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

下载数据

文件	
	证书 PL CN50 COB 1400 G2 ENEC 181121

产品数据表

	CAD数据 PL CN50 COB G2 STEP 160321
	CAD数据 PL CN50 G2 STEP 041121
	IES data PL CN50 COB 1400 940 40D G2.1 IES 120522

物流数据

产品代码	产品描述	包装单位 (件/单位)	尺寸 (长 x 宽 x 高)	体积	毛重
4052899621329	PL-CN50-COB- 1400-940-40D-G2	箱 20	268 mm x 110 mm x 138 mm	4.07 dm ³	2156.00 g

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时，按一个或多个整件数下单。

免责声明

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.