

FX-QMS-G1 -TU16H12-300

Surface slim profile 12x16 mm | LED 软灯带配件

产品特点

- Compatible with TEC Flex






产品优势

- 经过氧化处理，铝型材坚固、耐腐蚀

产品数据表

技术参数

尺寸和重量



长度	3000 mm
产品重量	42000 g
宽度	160 mm
高度	120 mm

物流数据

商品编码	76042990900
------	-------------

Environmental information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (RECh)	
Date of Declaration	30-08-2022
Primary Article Identifier	4052899448964
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

下载数据

文件	
	Product Datasheet Specification Sheet_Slim Track FX-QMS-G1-TU16H12-300 (EN)
	小册子 Light is freedom of design (EN)
	CAD数据 CAD file slim profile TU16H12
	Eulumdat Eulumdat_FX-QMS-G1-TU16H12-300_CFDL
	Eulumdat Eulumdat_FX-QMS-G1-TU16H12-300_CFDB

Ecodesign regulation information:

- This product is considered to be a "containing product" in the sense of Regulations (EU) 2019/2020 and (EU) 2019/2015.
- Tolerances of the reported values, are according to LED Modules Performance standard IEC/EN 62717.
- In general, the replacement of the contained light sources without permanent damage to the product with the use of common available tools is possible in the final application when they can be dismantled from the installation environment and substituted for the necessary number of light sources restoring its full electrical/mechanical/thermal/optical functionality by means of a professional installer.In the contrary, and limited to the LINEARlight Flex Diffuse, LINEARlight Rigid Finesse, GINO LED Flex Diffuse and LUMINENT Milky product families, the contained light source is an integrated part of the containing product and its removal can only be done by causing a permanent damage to the containing product due to its tight mechanical, electrical, optical, thermal interaction and/or environmental protection with or from the containing product. Therefore, a replacement of the light source with the use of common available tools is not justified.
- Dismantling of light sources from containing products at end of life: Containing products with light sources which are scalable in length can be cut to the length of the contained light source and if applicable mechanically detached from protective and/or optical covers. Containing products shall be separated from building material and/or from other additional mounting accessories by means of a professional installer.Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

产品数据表

物流数据

产品代码	产品描述	包装单位 (件/单位)	尺寸 (长 x 宽 x 高)	体积	毛重
4052899448964	FX-QMS-G1 -TU16H12-300	箱 20	3020 mm x 100 mm x 100 mm	30.20 dm ³	9420.00 g

这里所提到的产品编码代表最小订购数量。一个整件包装含有一个或多个单一产品。请您在下单时，按一个或多个整件数下单。

可选择性配件

产品描述	配件名称	配件代码
FX-QMS-G1 -TU16H12-300	FX-QMS-G1 -CFDB-300	▶ 4052899446991
FX-QMS-G1 -TU16H12-300	FX-QMS-G1 -EFGP-TU16H12LS	▶ 4052899449183

免责声明

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.