

PrevaLED Linear OP

线型LED 模组



产品特点

- 模块发光效率：高达160 lm/W
- Color temperature: 3,000 K, 4,000 K or 6,500 K
- LED module in 14 mm width, 489 mm length, Luminous flux on: 800 lm
- LED module in 14 mm width, 1095 mm length, Luminous flux on: 1600 lm
- 初始颜色一致性： ≤ 3 SDCM
- Average lifetime (L80 B50): $> 50,000$ h (temperature at $T_c = 75^\circ\text{C}$)
- CE, UKCA certified
- 显色指数 R_a : 80
- For indoor application

产品优势

- Design for slim and flat luminaire fixture
- Wide range of light colors
- High homogeneity thanks to LED optical lens

应用领域

- Office
- 酒店
- Education
- 商店
- 工业

产品系列数据表

应用建议

更多详细应用信息和图形,请参阅产品数据表。

数据表文本

- The LED module itself and all its components must not be stressed mechanically.
- Installation of LED modules (with power supplies) needs to be made under consideration of all valid regulations and norms.
- The modules are intended for operation only with matching OPTOTRONIC , ICUTRONIC and ELEMENT.
- Pay attention to standard ESD precautions when installing the module.
- Max. Voltage U-OUT = 60V for operation on SELV LED control gear.
- The final luminaire assembled with modules must be well packaged with carton.

销售和技术支持

销售和技术支持 www.osram.cn

Ecodesign regulation information:

Separate control gear and light sources must be disposed of at certified disposal companies in accordance with Directive 2012/19/EU (WEEE) in the EU and with Waste Electrical and Electronic Equipment (WEEE) Regulations 2013 in the UK. For this purpose, collection points for recycling centres and take-back systems (CRSO) are available from retailers or private disposal companies, which accept separate control gear and light sources free of charge. In this way, raw materials are conserved and materials are recycled.

参考资料/链接

* For more information on the multi-level guarantee and the terms and conditions of the guarantee visit <https://www.inventronics-light.com/multilevel-guarantees>

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。