

LEDDriving HLT BRIGHT H7

LEDDriving high and low beam lamps for truck



Cool White color temperature of 6,000 K

日光效果下视野更好



超高亮度

Up to +300% compared to minimum ECE R112. More light allows to see farther and therefore react sooner. Signs, obstacles and hazards can be recognized sooner



用于取代传统H7远光灯和近光灯的LED

通过优化光分布减少眩光



H7 LED replacement for 24V

LEDDriving HLT BRIGHT replacement lamps offer a modern and intense light with a color temperature of up to 6,000 Kelvin. These replacement lamps are suitable for conventional H7 high and low beam lamps. LEDDriving HLT BRIGHT for high and low beam off-road applications are 24 V compatible and stand out with superior brightness, high compatibility, easier installation due to integrated driver and no radio disturbance. The pair of lamps comes with a 4-year OSRAM guarantee. For precise guarantee conditions please refer to www.osram.com/am-guarantee. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

产品系列数据表

技术参数

产品描述	电参数					光度数据
	功率输入	标称电压	标称功率	输入功率容许偏差	测试电压	光通量
LEDriving HLT BRIGHT \triangleq H7	18 W	24 V	18 W	$\pm 20\%$	28.0 V	1700 lm




		Physical Attributes & Dimensions		
产品描述	光通量容许偏差	灯头 (标准名称)	长度	直径
LEDriving HLT BRIGHT \triangleq H7	$\pm 20\%$	PX26d	76.2 mm	14.0 mm

产品描述	寿命	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)		
	使用寿命 Tc	Primary Article Identifier	Candidate List Substance 1	CAS No. of substance 1
LEDriving HLT BRIGHT \triangleq H7	2000 hr	4062172379793	Lead	7439-92-1

产品描述	Safe Use Instruction	Declaration No. in SCIP database
LEDriving HLT BRIGHT \triangleq H7	The identification of the Candidate List substance is sufficient to allow safe use of the article.	e7d37971-6b5b-4773-9e3c-0ba8866799a3

产品系列数据表

下载数据

文件	
	User instruction LEDriving HLT BRIGHT
	User instruction GPRS_Safety symbols instructions
	Brochures LEDriving Retrofits - Exchange overview (EN)

安全建议

Application advice:For more detailed application information and graphics please see product datasheet and user manual.

应用建议

更多详细应用信息和图形,请参阅产品数据表。

免责声明

更改恕不另行通知。遗漏错误不承担任何责任。总是确保使用最新的信息。